



pinturas de la peña
fábrica de pinturas

WATERBORNE SATIN VARNISH

Waterborne Satin Varnish - Universal

Page 1 de 2

Acrylic varnish special for wood, which to obtain a satin finish; it can be applied both indoors and outdoors and on funds base water or solvent. It protects wood from external aggressions moisture and ultraviolet radiation has great resistance to yellowing and the quartering.

Features



Color	Transparent
Finishing	Satin
Specific weight	1,03 +/-0,02 gr./cc.
Viscosity on having trippled	95 +/- 5 K.U. a 25 °C
Shine to 60°	48 - 52 U.B.
Shine to 20°	14 - 16 U.B.
Fixed material	35 % +/- 3
Performance	11 - 12 m ² /lt
Drying time at touch	1 hour, depending on temperature and HR
Treat	21 days
Repainting	24 hours
Diluent	Freshwater (maximum dilution 5-10%)
Packaging	750 ml and 4 Lt containers
Conservation	Keep away from extreme temperatures

Application

Your application may be to brush, roller or projected to gun. Painted surfaces must be completely clean, free from dust or grease, bearing in mind that you do not apply at temperatures below 5°C or higher than 35°C.

Composition

Water, emulsions, dioxide of titanium, calcium carbonate and other materials chosen for this product.

NON-PAINTED SURFACES OR NEWS

Wood and agglomerate. Apply two or three coats of the product undiluted by lightly sanding between hands and remove the dust.

ALREADY PAINTED SURFACES

In good condition: gently sand the surface, remove dust and applied as new surfaces. IN bad state: completely remove the painting, prepare the surface and apply as is if you were a new surface.

Suitable for use domestic, not suitable for children.

Cautions

- S2 Keep out of reach of children
S23/24/25 Do not breathe vapors and avoid contact with eyes and skin.
S51 Use in well ventilated locations.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com





pinturas de la peña
fábrica de pinturas

WATERBORNE SATIN VARNISH

Waterborne Satin Varnish - Universal

Page 2 de 2



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

*Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)*

*t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com*

Master
Internacional
de Empresas

