



pinturas de la peña
fábrica de pinturas

PLASTIC PAINT P-17

Matt Plastic Paint indoors and outdoors

Página 1 de 2

Interior-Exterior matte plastic paint formulated with acrylic copolimeras emulsions with a good balance between opacity flexibility and finish both in white and in colors. It is permeable to interior vapors and impervious to exteriors.

Suitable for the decoration and protection of masonry surfaces in general, both interior and exterior wich are not problematic.

De 4 a 6 horas mínimo, máximo sin límite

Features



Color	White
Finish	Matt
Specific Weigth	1,57 +/-0,05 gr./cc.
Viscosity at time of packaging	110 K.U. a 25 °C
Fixed matter %	60 % +/-2
Volume solids %	39 % +/-2
Performance	10 a 12 m ² /lt per coat depending on the state of the surface
Wet film recommended thickness	80-100 micras per coat
Dry film recommended thickness	30-35 micras per coat
Dr-to-touch time	40 - 60 minutes
Curing time	21 days
Recoat	4-6 hours
Diluent	Clean water
Presentation	Cans of 14 liters
Conservation	Keep away from extreme temperatures
COV'S	Cat A/a (legal limit 30 g/l) Maximun content 30 g/l

Application

It can be applied on any construction material, cement, plaster, etc. Its application can be brushed, roller or sprayed. Before application the facing must be completely clean and dry. It should not be applied at temperatures below 5 °c or above 35 ° C.

Composition

Water, acrylic copolimera emulsion, titanium dioxide, calcium carbonates and other loads chosen for this product.

Suitable for domestic use. Keep out of reach of children.

Cautions

P101 If medical advice is needed, have the container or label handy.

P102 Keep out of reach of children.

P103 Read the label before use.

P501 To eliminate the contents/container according to the current legislation of waste treatment (law 22/2011).



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com



Master
Internacional
de Empresas



pinturas de la peña
fábrica de pinturas

PLASTIC PAINT P-17

Matt Plastic Paint indoors and outdoors

Página 2 de 2

EUH208 contains 2-octyl-2h-Isotiazon-3-ona.

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-ona [EC No. 247-500-7]; 2-methyl. 2h-Isothiazol-3-ona [EC No. 220-239-6] (3:1) may cause an allergic reaction.

According to Royal Decree 363/1995 (Directive 67/548/EEC) and Royal Decree 255/2003 (Directive 1999/45/EC), this is not classified as a dangerous product. Safety data sheet available for professional user on request.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com



Master
Internacional
de Empresas