



pinturas de la peña  
fábrica de pinturas

## ANTI-CONDENSATION INSULATING PAINT

Matte Plastic Paint prevents the cold wall effect

Page 1 of 2

Anti-condensation paint specially designed to reduce the phenomenon the cold wall effect, which is usually the cause of the appearance of areas blackened by the proliferation of mold.

Condensation moisture occurs when inside a house there is water vapor and comes into contact with cold walls (more pronounced phenomenon in winter)

It also provides a good thermal insulation capability when formulated with glass hollow beads of low thermal conductivity.

Specially suitable for decoration in ceilings and vertical walls inside and outside (plaster, cement, etc.), where there are condensation problems or some thermal insulation is desired.

Non-toxic, with very low odor and non-flammable.

### Features



Color	White
Finishing	Slightly textured matte
Specific weight	0.86 +/- 0,05 gr./cc.
Viscosity at time or packaging	130 K.U. to 25 °C
Fixed material %	52 % +/- 3
Solids in volume (theoretical)	60 % +/- 3
Performance	1 a 2 m <sup>2</sup> /Kg depending on the state of the wall and the desired thickness
Drying time to the touch	40 to 60 minutes
Total curing	21 days
Repainted	4 to 6 hours minimum, maximum o limit
Thinner	Sweet water
Presentation	750 ml and 4 lt. containers
Conservation	Keep away from extreme temperatures.
COV'S	Cat A/a (legal limit 30 g/l) content max 25 g/l

### Application

It can be applied to any construction material, plaster, cement, etc. Its application can be to brush or roller of short hair or even spatula or plain steel. It can be repainted with any plastic paint. Before application, the surface must be completely clean and dry. It should not be applied at temperatures below 5°C or above 35°C.

**Suitable for household use, not suitable for use in children.**

### Cautions

- P101 If medical advice is needed, have the container or label on hand.  
 P102 Keep out of reach of children.P103Leer la etiqueta antes del uso.  
 P501 Delete the content and/or its container through the Selective collection system enabled in your municipality.



Distribuidor Oficial de:

*Nota: Esta información está basada en el estado actual de nuestros conocimientos, son datos orientativos de carácter general. Describen nuestros productos y orientan al usuario sobre su aplicación y empleo. Debido a la gran variedad de condiciones de uso y soportes no debe tomarse como base de garantía ni objeto de responsabilidad.*

[www.delapenia.com](http://www.delapenia.com)

Fábrica y oficinas



Trofeo  
CC100  
Compromiso  
a la Calidad

Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )

t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)





pinturas de la peña  
fábrica de pinturas

## ANTI-CONDENSATION INSULATING PAINT

Matte Plastic Paint prevents the cold wall effect

Page 2 of 2

EUH208 contains 2-octil-2H-isothiazon-3-one. Mixture of: 5-chloro-2-methyl-2H-isothiazole-3-one [EC No. 247-500-7]; 2-metil.2H-isothiazole-3-one [EC No. 220-239-6] (3:1). It can cause an allergic reaction.

*In accordance with R.D. 363/1995 (Directive 67/548/EC) and R.D. 255/2003 (Directive 1999/45/EC), the product is not classified as hazardous. Safety data sheet available to the professional user requesting it.*



Distribuidor Oficial de:

**FESTOOL**

*Nota: Esta información está basada en el estado actual de nuestros conocimientos, son datos orientativos de carácter general. Describen nuestros productos y orientan al usuario sobre su aplicación y empleo. Debido a la gran variedad de condiciones de uso y soportes no debe tomarse como base de garantía ni objeto de responsabilidad.*

**[www.delapenia.com](http://www.delapenia.com)**

Fábrica y oficinas



Trofeo  
CC100  
Compromiso  
a la Calidad

Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )

t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)



Master  
Internacional  
de Empresas