



pinturas de la peña
fábrica de pinturas

PEÑA AKRIL GLOSSY®

Glossy Acrylic Paint for Exigent Works

Page 1 de 2

PEÑA AKRIL is a semi-glossy plastic paint made with the best Vinyl copolymer emulsions and Rutile titanium dioxide. Due to its painstaking manufacturing, it has great flexibility, excellent adhesion, totally waterproof, and anti-mildew additives and algacide which protect against verdigrin and mold.

The plastic painting PEÑA AKRIL as a result of the great number of technical test which it has been proved we can ensure that it meet the perfect conditions for decoration and waterproofing (vertical) for interior and exterior (*). Its finish is very beautiful and semi-glossy, obtaining a great whiteness and highly covering.

Features



Color	White and colors of the chart (*)
Finishing	Glossy semi-brilliant
Shine to 85°C	> 65 %
Specific weight	1,28 +/- 0,05 gr./cc.
Viscosity on having trippled	95 K.U. to 25 °C
Fixed material	54 % +/- 5
Solid on volume	42 % +/- 5
Performance	8 - 10 m ² /Kg per coat depending of the state of the surface
Minimum dry thickness	31-35 microns per coat
Drying time	40 - 60 minutes
Treat	21 days
Repainting	8 - 10 hours minimum, maximum without limit
Diluent	Fresh water
Presentation	1, 5, 10, and 18 Kg. containers
Conservation	Keep away from extreme temperatures
COV'S	Cat A/a (legal limit 100 g/l) max. cont. 30 g/l

Application

Can be applied on any building material, plaster, cement, plaster, etc. Application may be to brush, roller or projected to spray-gun. Before application the facade must be completely clean and dry, taking into account that it should not be applied at temperatures below 5 °C or above 35 ° C.

Composition

Water, emulsions, Vinyl copolymers, special additives, dioxide of titanium, calcium carbonate and other materials chosen for this product.

PAINT WITH CERTIFICATE OF APPROVAL BY GEOCISA LABORATORIES
Suitable for use domestic, not suitable for children.

Cautions

- S2 Keep out of reach of children
S23/24/25 Do not breathe vapors and avoid contact with eyes and skin.
S51 Use in well ventilated locations.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com



Master
Internacional
de Empresas



pinturas de la peña
fábrica de pinturas

PEÑA AKRIL GLOSSY®

Glossy Acrylic Paint for Exigent Works

Page 2 de 2

(*) *In strong colors, ask for the outdoor stability.*

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Distribuidor Oficial de:

FESTOOL

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com

Master
Internacional
de Empresas

