



pinturas de la peña  
fábrica de pinturas

## BASE 2 SATIN (MEDIUM)

Special Acrylic Satin Paint for Dyeing System (Mix machine)

Page 1 de 2

The acrylic paint BASE 2 SATIN is formulated with emulsions most advanced and first quality, as well as other raw materials, which gets a great product of high performance, hardness, perfect coverage for its wealth of dioxide of titanium and good resistance to weather and rubbing, by its great amount of emulsion.

BASE 2 SATIN acrylic paint, possesses great flexibility, good adhesion and resistance to the alkalinity of the cement, it is vapor-permeable indoor and waterproof to the outdoor, and also has a great power covering, leaving a perfect finish.

Calibrated and tested for use as opaque base in Pinturas de la Peña dyeing system.

### Features

Color	White medium
Finishing	Satin
Specific weight	1,28 +/-0,05 gr./cc.
Viscosity at time of packaging	95 K.U. to 25 °C
Fixed material	45 % +/- 1
Performance	8 - 10 m <sup>2</sup> /Kg
Drying time at touch	45 - 60 minutes
Treat	21 days
Repainting	4 - 6 hours
Diluent	Water (5 - 10 %)
Packaging	0,8, 4,3 and 16,30 Kg. container
Conservation	Keep away from extreme temperatures



### Application

It is an also indicated product outdoors and indoors, it can be applied to cement, plaster, concrete, brick, stone, etc. It is particularly suitable as white base coloring in any painting system that is based on two or three bases.

Brush, paint roller or "Airless" spray gun. The surfaces must be clean and dry. Don't apply under temperatures lower than 5°C or higher than 35°C.

### Composition

Water, emulsions, dioxide of titanium, calcium carbonate and other materials chosen for this product.

**Suitable for use domestic, not suitable for children.**

### Cautions

S2	Keep out of reach of children
S23/24/25	Do not breathe vapors and avoid contact with eyes and skin.
S51	Use in well ventilated locations.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

[www.delapenia.com](http://www.delapenia.com)

Factory and offices



Trofeo  
CC100  
Compromiso  
a la Calidad

Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )

t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)





pinturas de la peña  
fábrica de pinturas

## BASE 2 SATIN (MEDIUM)

Special Acrylic Satin Paint for Dyeing System (Mix machine)

Page 2 de 2



Distribuidor Oficial de:

**FESTOOL**

*Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.*

**[www.delapenia.com](http://www.delapenia.com)**

**Factory and offices**



Trofeo  
CC100  
Compromiso  
a la Calidad

*Ctra. Orgaz, s/n  
Apdo. 25  
45400 Mora ( Toledo )*

*t: +34 925 300 409  
f: +34 925 341 082  
e: [info@delapenia.com](mailto:info@delapenia.com)*

Master  
Internacional  
de Empresas

