



pinturas de la peña
fábrica de pinturas

PEÑAIMP

Primer for Galvanized and Bad Adhesion Surfaces

Page 1 de 2

Multi-purpose paint, made special acrylic emulsions to achieve a great anchor. It serves as a primer or finish for galvanized, aluminum, PVC, tiles, fund for wood and other materials with low or no adherence by its nature little porous or glazed, it provides be repainted with the most of water or solvent-based paints.

Features



Color	White
Finishing	Silky Matt
Specific weight	1,55 +/-0,05 gr./cc.
Viscosity on having trippled	105 K.U. to 25 °C
Fixed material	71 %
Performance	4 - 6 m ² /Kg
Drying time	60 - 90 minutes
Treat	21 days
Repainting	21 hours
Diluent	Water (dilución 5 - 10 %)
Presentation	1 and 5 Kg. containers
Conservation	Keep away from extreme temperatures

Application

The surface to be painted it must be completely clean without oxides, fat, dust or traces of paint bad adhesion. It can be applied by brush, roller or spray. Used as diluent water (5-10% max.). When your application is on PVC lightly sand this material in order to facilitate adherence on the same. Before applying the coat check that it is fully dry (24-48 hours depending on the temperature and the environment).

Due to the wide variety of existing materials and the enormous possibilities of finishes is strongly recommended to do preliminary tests with the system chosen by the customer.

Composition

Water, emulsions copolymers special, dioxide titanium, calcium carbonates and other loads selected for this product.

Suitable for use domestic, not suitable for children.

Cautions

- S2 Keep out of reach of children
S23/24/25 Do not breathe vapors and avoid contact with eyes and skin.
S51 Use in well ventilated locations.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)

t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com





pinturas de la peña
fábrica de pinturas

PEÑAIMP

Primer for Galvanized and Bad Adhesion Surfaces

Page 2 de 2



Distribuidor Oficial de:

Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on its application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Factory and offices



Trofeo
CC100
Compromiso
a la Calidad

*Ctra. Orgaz, s/n
Apdo. 25
45400 Mora (Toledo)*

*t: +34 925 300 409
f: +34 925 341 082
e: info@delapenia.com*

Master
Internacional
de Empresas

