

# **ANCIENT EFFECT**

High-End Decor Paint of Singular Finish

Page 1 de 2

pinturas de la peña fábrica de pinturas

A very special product, of very easy application and incredible results. Decorative system granting surfaces an ancient effect, combining the glaze effect with strokes of white particles that can be combined, optionally, with brown particles.

Complete system made of three components:

- 1° Ancient effect base: specially designed to facilitate application and obtain maximum performance.
- 2º Neutral base ancient effect
- 3º Ancient effect toner in colors (in order to easily obtain the colors of the chart)





### **Features**

Color	Translucent white (to be dyed according to colors of the chart)
Aspect	Medium viscosity white clay with particles
Finish	Low satin
Specific weight	1'05 +/-0'05 gr./cc.
Viscosity at time of packaging	120 +/-5 K.U.
Fixed matter %	15% +/- 2
Coverage	8 to 10 m <sup>2</sup> /kg (depending on the absorption of the surface)
Dry-to-touch time	12 hours / 20° C. Humidity 60%
Curing time	21 days
Recoat	Minimum 8 hours. Maximum no limit
Thin with	Clean water (packed ready to use)
Dyes	Universal dyes De la Peña and pain-mixing system
Presentation	2'5 and 10 kg cans (base). 250 gr (toner)
Conservation	Keep away from extreme temperatures

## **Application**

- 1° Surface preparation: the surface to be painted should be clean, dry and free of dust and grease. Apply a first coat of PeñaAkril satin paint (white or the desired colour). Allow to dry at least 24 hours.
- 2° Obtaining the colour: dye SeaWaves Effect with water-borne or universal De la Peña dyes using the desired colour and mix until obtaining a homogenous hue.
- 3° Application: with a short nap roller. Try to apply a homogenous coat. Afterwards, create the desired effect with the special tools (rollers, sponges, gloves, etc.). Depending on the temperature and the humidity, you have around 30 minutes before the product dries and stops being manageable. Therefore, it is recommendable not to apply it to large surfaces and not to make straight passes in order to conceal the joint points.

#### **Product composition**

Water, acrylic emulsions and special aditives chosen for this product.

## Suitable for domestic use. Keep out of reach of children.

### **Cautions**


- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P501 Dispose of contents and / or their container according to the separated collection system used in your municipality.

EUH208 Contains 2-octyl-2H-isothiazon-3-one.



Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com











# **ANCIENT EFFEC**

High-End Decor Paint of Singular Finish

Page 2 de 2

pinturas de la peña fábrica de pinturas

Mixture of: 5-chloro-2-methyl-2H-isothiazolin-3-one [EC no. 247-500-7]; 2-methyl.2H-isothyazol-3-one [EC no. 220-239-6] (3:1).

May produce an allergic reaction.

According to Royal Decree 363/1995 (Directive 67/548/EEC) and Royal Decree 255/2003 (Directive 1999/45/EC), this is not classified as a dangerous product. Safety data sheet available for professional user on request.



Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com





