

The MONO-layer plastic paint is formulated with advanced technology emulsions with which you get a product of great quality, high performance and good weather resistance. It has great flexibility, good adhesion and resistance to the alkalinity of the cement. It is permeable to interior vapors and impervious to exteriors. It is an equally suitable product for indoor and outdoor painting.

Features

Color	White and another colors
Finish	Matt
Specific weight	1,62 gr./cc.
Viscosity at time of packaging	105K.U. a 25°C
Fixed matter	66%
Performance	11-12 m ² /lt.
Total drying time	40-60 minutes
Curing	21 days
Recoat	8-10 hours
Diluent	Water, so it is considered fire retardant
Presentation	Cans of 4 lt and 2,5 Lts.
Conservation	Keep away from extreme temperatures



Application

It can be applied on any construction material, cement, plaster, etc. Its application can be brushed, roller or sprayed. Before application, the facing must be completely clean, dry and free of chips or improperly adhered materials. Do not apply to temperatures below 5 °C or above 35 °C.

Composition

Water, emulsions, titanium dioxide, calcium carbonates and other loads chosen for this product.

Suitable for use domestic, not suitable for children.

Cautions

- S2 Keep out of reach of children
 S23/24/25 Do not breathe vapors and avoid contact with eyes and skin.
 S51 Use in well ventilated locations.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.