



pinturas de la peña
fábrica de pinturas

ACRYLIC P-21

Acrylic Paint for indoor and outdoor

Page 1 of 1

Acrylic matt paint specially formulated for indoor and outdoor decoration, with a perfect balance between loads and emulsions which give it a good resistance to friction and allows sweat high way. It has an excellent whiteness, good power, dry hiding and a good acceptance of colour.

Features



Colour	White
Finishing	Matt
Specific weight	1,71 +/-0,05 gr./cc.
Viscosity at time of packaging	105 K.U. to 25°C
Fixed material %	71% +/- 5
Solid on volume %	42% +/- 5
Performance	5 - 6 m ² /kg per coat depending of the state of the surface
Drying time at touch	1 - 2 hours
Treat	21 days
Repainting	10 - 12 hours minimum, maximum without limit
Diluent	Fresh water
Packaging	5 Kg. and 23 Kg. containers
Conservation	Keep away from extreme temperatures
COV'S	Cat A/a (legal limit 30 g/l) max. cont. 25 g/l

Application

It can be applied on any building material, plaster, cement, plaster, etc. Your application can be by brush, roller or projected airless spray, etc. Before application, the coating must be clean and completely dry. You do not apply at temperatures below 5°C or higher than 35°C. Stir until homogenization of the product.

It is recommended to apply a first layer of diluted with 10-15% of water using brush or roller and 20-25% if the application is with "Airless". Do not apply outside if rain is expected within 12 hours. Clean tools with water immediately after use.

Composition

Water, emulsion acrylic copolymer, titanium dioxide, carbonates of calcium and other loads selected for this product.

Suitable for use domestic, not suitable for children.

Cautions

- S2 Keep out of the reach of children.
 S23/24/25 Do not breathe vapors and avoid contact with eyes and skin.
 S51 Use only in well-ventilated areas.

According to the Royal Decree 363/1995 (Directive 67/548/EC) and the Royal Decree 255/2003 (Directive 1999/45/EC), not this classified as dangerous product. Data sheet security available to the professional user who requests it.



Distribuidor Oficial de:

Note: This information is based on our current knowledge, so the piece of information is general. It describes our products and gives an orientation on how to apply and use our products. Due to the big variety, use conditions and surfaces, it cannot be taken as warranty or object of liability.

Address (Factory and offices)
 Ctra. Orgaz, s/n
 Apdo. 25 - 45400 Mora (Toledo)
 Ph: +34 925 300 409 f: +34 925 341 082
 e-mail: info@delapenia.com



Máster
 Internacional
 de Empresas



Empresa Certificada en fabricación
 y diseño de pinturas al agua.

www.delapenia.com



Trofeo CC100
 Compromiso a
 la calidad

Delegation
 C/Manzanares, 1
 13250 Daimiel (Ciudad Real)
 Ph: +34 926 851 102
 e-mail: info.daimiel@delapenia.com