

RUSTIC EFFECT

High-decoration painting with rustic finish

Page 1 of 2

Interior decorating System, which gives the walls a rustic and at the same time elegant effect. Easy and quick to apply, can be used on smooth or rough surfaces by concealing the small defects of the

Its balanced formulation makes this product one of the best in the market in its category, both in terms of finish and ease of work. It also has a high durability and flexibility characteristics that make it suitable for artistic works (on canvas, wood, etc.).

The system consists of two products: neutral base or paste and colored finish wax.





Features

Color	white
Appearance	High viscosity white paste
Finish	Matt particular touch
Specific weight	1,43 +/- 0,05 gr./cc.
Fixed matter	64 % +/- 2
Performance	1 to 2 m ² / kg (depending on the desired finish)
Total drying time	12 - 14 hours
Curing time	21 days
Wax termination	Minimum: 8 hours; maximum: without limit
Diluent	Packaging to use (water)
Presentation	(Base) Cans of 23, 12 and 4 Kg (Wax) Cans of 2,5 Kg and 600 Gr
Conservation	Keep away from extreme temperatures

Application

The product is prepared for use, it is not advisable to dilute, its application can be with plastic or steel trowel, depending if you want a rougher or smoother finish. It should be applied homogeneously throughout the surface, leaving a regular thickness. It is necessary to work on surfaces not exceeding 5 m2. When the base is completely dry (minimum 24 hours), apply the tinted wax with a cloth or gauze (type crankpins) with circular movements, ensuring that there is no uncovered area. The surfaces to be treated must be clean of saltpeter, grease, foreign elements and completely free of moisture.

It is advisable to anchor the walls before applying the rustic effect with smooth coating of the rock (white smooth Rugopeña), to favour the anchorage and regularize the absorption of the surface. It should be applied at temperatures between $5 \, ^{\circ}$ C and $35 \, ^{\circ}$ C.

Cleaning utensils

Cleaning of the working tools will be done with water immediately after use.

Suitable for domestic use. Keep out of reach of children.


Cautions

- P101 If medical advice is needed, have the container or label handy.
- P102 Keep out of reach of children.
- P103 Read the label before use.
- P501 Delete the content and/or its container through the selective collection system enabled in your municipality.



Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com









RUSTIC EFFECT

High-decoration painting with rustic finish

Page 2 of 2

EUH208 Contents 2-octil-2H-isotiazon-3-ona.

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3-ona [EC No. 247-500-7]; 2-methyl. 2h-Isothiazol-3-ona [EC No. 220-239-6] (3:1) may cause an allergic reaction.

According to Royal Decree 363/1995 (Directive 67/548/EEC) and Royal Decree 255/2003 (Directive 1999/45/EC), this is not classified as a dangerous product. Safety data sheet available for professional user on request.



Notice: This information is based on the current condition of our knowledge, and is of general character. It describes our products and orientates the user on it application and employment. Due to the big variety, use conditions and supports it must think neither as base or guarantee nor object of responsibility.

www.delapenia.com

Ctra. Orgaz, s/n Apdo. 25 45400 Mora (Toledo)



